

Material Safety Data Sheet

May be used to comply with OSHA's
Hazard Communication Standard, 29 CFR 1910.1200

IDENTITY (As used on labels and List)

EXPRESS NL301

NPCA Hazardous Materials Identification System

Specific Hazard	Personal Protection
4-Severe	X-Ask a supervisor
3-Serious	A-Safety Glasses
2-Moderate	B-Goggles, Gloves
1-Slight	C-Goggles, Gloves, Apron
0-Minimal	D-Goggles, Gloves, Apron, & Faceshield

Health (3) **Reactivity (1)**
Flammability (0) **Personal Protection (B)**

SECTION I

MFGR'S NAME AND ADDRESS:

Newline Industries Llc.
1030 West Amelia Street Suite D
Orlando, FL 32805

EMERGENCY TELEPHONE NUMBER:
FOR ADDITIONAL INFORMATION

800-535-5053
407-480-5464

Date Prepared:
02/02/2010

SECTION II - HAZARDOUS INGREDIENTS/ IDENTITY INFORMATION

Hazardous Components	OSHA PEL	ACGIH	TLV	Other	% Optional
Specific Chemical Identity	LIMITS				
Common Name(s)	Recommended				
Monoethanolamine, Colamine	3ppm	3ppm			10.00
CAS # 141-43-5					
*2-Butoxyethanol	50ppm	75ppm			60.00
CAS # 111-76-2					

*This mixture contains 60.00% of 2-Butoxyethanol which subject to the reporting requirements of section 313 of Title III of the Superfund Amendments of Reauthorization Act of 1986 and 40 CFR, Part 372.

SECTION III-PHYSICAL/CHEMICAL CHARACTERISCS

BOILING POINT (F) Over 212 F	SPECIFIC GRAVITY (H2O=1) 0.985
VAPOR PRESSURE (mm Hg.) N/A	MELTING POINT N/A
VAPOR DENSITY (air = 1) N/A	EVAPORATION RATE Less than 1
SOLUBILITY IN WATER 100%	(Butyl Acetate = 1)
APPEARANCE AND ODOR: Clear, colorless liquid with a mild odor.	

SECTION IV- FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (METHOD USED)	FLAMMABLE LIMITS	LEL	UEL
None	N/A	N/A	N/A

EXTINGUISHING MEDIA: Form or Carbon Dioxide Dry Foam

SPECIAL FIRE FIGHTING PROCEDURES: Use self-contained breathing apparatus with a full facepiece operated in pressure-demand or other positive pressure mode when fighting fires

UNUSUAL FIRE AND EXPLOSION HAZAORDS: Vapors are heavier than air and may travel along the ground or be moved by ventilation and ignited by heat, pilot lights, other flames, and ignition sources at locations distant from material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively.

